PERFORMANCE BULLETIN



YPB#: PB_ALM_Escape165CS_F30LA_2013-09-09_ALM

Aluma
Length
Beam
Dry Wei
Maximu
Fuel Cap


ALUMACRAFT

Boat Manufactured By:

Alumacraft • 315 West St. Julien Street • St. Peter, MN 56082 507-931-1050 • www.alumacraft.com

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	2.7	0.2	13.50
1500	4.3	0.3	14.33
2000	5.3	0.5	10.60
2500	6.2	0.7	8.86
3000	7.2	0.9	8.00
3500	9.0	1.1	8.18
4000	11.7	1.5	7.80
4500	15.1	1.7	8.88
5000	17.5	2.0	8.75
5500	19.6	2.8	7.00
5800	20.8	3.1	6.71



Test Date 9/9/13

Alumacraft® Escape 165 CS

Length	16' 6"
Beam	6' 4"
Dry Weight (Boat Mfr. Pub)	696 lbs
Maximum HP	50
Fuel Capacity	Portable Tank
Weight as Tested	1,582 lbs

F30LA

Horsepower	30 HP
Induction	EFI
Displacement	45.6 cu in
Weight	214 lbs
Gear Ratio	2.00

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	1/2" Below Boat Bottom

PROPELLER/S

Series	Aluminum "G" Series
Diameter/Pitch	12-1/4 x 8
Yamaha Part #	63D-45941-00-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	83 / 71° F
Elevation (in feet above sea level)	975'
Wind Velocity	5-10 mph

Comments: Test weight includes 4 gallons of fuel, 2 batteries, bow-mounted trolling motor, safety and test gear.

Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

For more information

Yamaha Motor Corporation, U.S.A.
OEM Division, Marine Group
1270 Chastain Road NW
Kennesaw. GA 30144 • (800) 88-YAMAHA

For other Performance Bulletins, visit www.yamaha-motor.com.

© 2013 Yamaha Motor Corporation, U.S.A. All rights reserved.