

**BULLETIN #: PE1088** 

**ENGINE: E90DPLAAA** 

**BOAT TYPE: Aluminum** 

**DATE OF TEST: 6/18/13** 



Bombardier Recreational Products Inc. 10101 Science Drive Sturtevant, WI 53177 www.evinrude.com



Alumacraft Boat Co. 315 W. Saint Julien St. St Peter, MN 56082 1-877-314-7756 www.alumacraft.com

## 2014 Alumacraft Pro 185

BOAT				
2014 Alumacraft Pro 185				
Material:	Aluminum			
Length:	18' 5"			
Beam:	86"			
Weight w/o Engine:	1100 LBS Dry			
Maximum HP:	115 HP			
Fuel Capacity:	20 Gallons			
Transom Height:	20" Shaft			
Steering:	Cable			



ENGINE				
Evinrude® 90 HP ETEC®				
Engine Type:	Inline 3 Cyl			
Horsepower:	90HP @ 5000 RPM			
Displacement:	79.1 Cu In			
Induction:	ETEC DF			
Operating Range:	4500-5500 RPM			
Weight:	320 LBS Dry Weight			
Gear Ratio:	2.00:1			

BRP Viper			
Material:	Stainless Steel		
Diameter/Pitch:	13 7/8" x 17"		
No. of Blades:	3		
Part Number:	763930		
MOUNTING HEIGHT			
Hole Position:	#2		
Jack Plate:	N/A		
AV Mounting:	N/A		

PERFORMANCE DATA					
RPM	MPH	GPH	MPG	RANGE	
700	3.1	0.10	30.5	549	
1000	4.3	0.20	21.5	387	
1500	6.0	0.80	7.4	134	
2000	7.6	1.70	4.5	80	
2500	14.5	2.40	6.0	108	
3000	20.0	3.10	6.5	116	
3500	25.6	4.10	6.2	112	
4000	30.6	5.35	5.7	103	
4500	34.6	6.40	5.4	97	
5000	38.9	7.70	5.0	91	
5200	41.3	7.80	5.3	95	
Range (Miles) Based On 90% Fuel Capacity					

TEST CONDITIONS		
Water Conditions:	Calm	
Wind Velocity:	5 MPH	
Air Temperature:	86° F	
Fuel Load:	Full	
Weight:	2 Men, Fuel, Safety/Test Gear	
	Trolling motor, 2 Batteries	

## **PERFORMANCE SUMMARY**

Top Speed: 41.3 MPH

Best Fuel Efficiency: 6.5 MPG with a range of 116 Miles @

20.0 MPH

Acceleration: 3.92 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2013 BRP US Inc. All rights reserved.

